

**Attorney Docket No. 74953/11664**

*Entitled:*

**REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM**

*Joint Inventors:*

Edwin K. RUNYON  
270 Halligan Avenue  
Worthington, OH 43085

Jess MURPHY  
845 Buehler Drive  
Delaware, OH 43015

Stephen RAUCH  
10603 Allen Road  
Pickerington, OH 43147

Joe POKOJ  
6693 Pine Hollow Drive  
Westerville, OH 43082

John C. STUTZ  
8116 Chutney Road  
Blacklick, OH 43004

*Assignee:*

Siemens Airfield Solutions  
977 Gahanna Parkway  
Columbus, OH 43085

*Submitted by:*

Eric D. Jorgenson  
Reg. No. 46,002  
Arter & Hadden, L.L.P.  
1100 Huntington Building  
925 Euclid Avenue  
Cleveland, OH 44115-1475  
(216) 696-1100

FILE NO. 74953/11664

PATENT

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM**

## REMOTE ACCESS OF AN AIRPORT AIRFIELD LIGHTING SYSTEM

### BACKGROUND OF THE INVENTION

#### 5 TECHNICAL FIELD OF THE INVENTION

This invention is related to airport airfield lighting systems, and more specifically, to systems which monitor such airfield lighting systems and remote access provided thereto via the Internet.

#### 10 BACKGROUND OF THE ART

The future of aviation is undergoing a massive technological change with the use of Global Positioning System (GPS) technology. This change not only affects large air carrier airports, but also the smaller general aviation airports located in remote areas or small towns. Higher levels of funding are also becoming more available for general aviation airports.

It is anticipated that changes in federal regulations under the FAA (Federal Aviation Administration) will stipulate that the FAA no longer buy and maintain the approach equipment. Equipment will be funded by the FAA, however, the equipment will need to be installed and maintained by local airport maintenance staff and/or out-sourced to a maintenance contractor for support. This change from a centralized federal program to a localized standalone operation presents a new problem for approach lighting systems for general aviation airports. Not only will the local airports be held responsible for the maintenance of the airfield lighting and related systems, but they will need to provide the support contracts. Furthermore, in those remote areas where technically-capable maintenance personnel may not be readily available, other means are needed to ensure that the airport has a safe and operational airfield lighting system.

What is needed is a system which provides local monitor and control of the general aviation airport airfield lighting system while also offering remote portal access to the local system by authorized users for periodic review of the system data which indicates the viability of the airport system. Furthermore, the local system needs an

automatic notification feature for automatically notifying selected users when system faults occur. Still further, what is needed is a centralized general aviation monitoring system which connects to monitor a number of remote general aviation airport airfield systems, including runway and approach lighting systems, etc., such that authorized  
5 individuals can access the remote systems from anywhere, and at any time.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
22

## SUMMARY OF THE INVENTION

The present invention disclosed and claimed herein, in one aspect thereof, comprises remote monitor and control of an airfield lighting system. A processing system  
5 local to the airport is provided in communication with the airfield lighting system for monitor and control thereof, the airfield lighting system producing airfield information for processing by the local processing system. The local processing system connects to a global communication network such that the airfield lighting system information is accessed from a remote location disposed on the global communication network.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

## BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying drawings in which:

5           FIG. 1 illustrates a block diagram of a remotely accessible general aviation monitor and control system;

          FIG. 2 illustrates a flow chart from the perspective of a customer/client when accessing the disclosed system;

          FIG. 3 illustrates a flow chart from the perspective of maintenance support  
10          personnel when accessing the disclosed system;

          FIG. 4 illustrates a flow chart of the operation of the airport notification system, according to a disclosed embodiment;

          FIG. 5 illustrates a flow chart of the operation of the remote airport monitor and control system;

15          FIG. 6 illustrates a flow chart of operation from the perspective of the control center a user accesses the disclosed system;

          FIG. 7 illustrates a user interface of an authorization web page to the control center website;

          FIG. 8 illustrates a follow-up web page to the authorization web page showing  
20          various data parameters which can be accessed by a user; and

          FIG. 9 illustrates a database structure, in accordance with a disclosed embodiment.

## DETAILED DESCRIPTION OF THE INVENTION

The disclosed system architecture consists of several components combined to effect a system that monitors the status of airfield lighting equipment, and reports status and failure condition information to a central control center. The control center then utilizes this information to dispatch service personnel to the airfield for corrective action. The control center also provides historical and trending analysis for the airfield equipment being monitored for the client.

The disclosed system is not limited to airfield lighting systems, but can accommodate any airport systems, including fire alarm systems, security systems, etc. In those situations where general aviation airports have conventional remote monitoring systems already in place, the disclosed system is operable to provide redundant control and measurement capability of the existing data points, or even displacing the conventional system in its entirety. For example, the FAA (Federal Aviation Administration) purchases and provides airfield equipment, e.g., approach lighting systems (ALS) and precision approach path indicators (PAPIs) for some, but not all, aviation airports, and the FAA currently elects to support (i.e., maintain and monitor) such approach systems for those selected airports. Regional FAA offices throughout the U.S. provide oversight of the respective ALS and PAPI systems utilizing a remote maintenance monitor (RMM) system for monitoring selected parameters of the regional airports. The associated RMM hardware and software of the FAA system is expensive. Where such an FAA implementation exists, the disclosed system can provide either redundant monitor and control capability of the various data points with access from the various networked entities, as will be described in greater detail hereinbelow, or preferably displace the FAA system entirely with a more robust and cost effective solution. In the least, substantial improvements in remote accessibility can be provided for the RMM data points via a redundant implementation of the disclosed system.

Referring now to FIG. 1, there is illustrated a block diagram of a remotely accessible general aviation monitor and control system, according to a disclosed embodiment. An airport 100 comprises a runway 102 which has associated therewith a number of airfield lighting system lights 104 whose electrical parameters are under control of a respective control and monitor unit 106. For example, the light interface control and monitor unit 106 may provide constant current control by way of a constant

current regulator (CCR). Other means may be used to control each of the lights 104 of the runway such as voltage control devices. Note that the disclosed architecture is not restricted to runway lighting systems, but can be implemented to monitor and control any airport systems connect thereto. Examples include, as indicated hereinabove, ALS and PAPI systems, RMM systems, runway edge identifier lights, rotating beacons, etc.

The light interface units 106 each connect to a server 108 via a communication path 107 to facilitate the communication of monitor and control information to and from the light interface units 106, and to store data parameters related to the airfield lighting system of that particular airport 100. The communication network 107 between the control units 106 and the server 108 can be any conventional architecture which provides such connectivity. The medium can be optical fiber, metal wire, and even communication signals which are modulated onto power signals for transmission over power cables (e.g., X10 technology). The server 108 connects to an airport network interface device 110 for communication via an external global communication network (GCN) 112, e.g., the Internet, and offers access to the remote airport 100 from any node connected thereto. The airport network interface device 110 can be that which accommodates any technology for providing such communication capabilities, for example, DSL, cable modem access, ISDN, analog modem, T1, etc.

It can be appreciated that where global access is provided via the GCN 112, more secure measures may be needed to prevent unauthorized access to the server 108 and connected systems of the remote airport 100. For example, a firewall system 114 may be implemented to prevent such unauthorized access. The firewall system 114 connects to the airport network interface device 110 such that all incoming communication traffic is routed therethrough, and then to the server 108 along a path 116. Although the firewall system 114 is illustrated as a separate block, it can be consolidated into the server 108 such that all incoming traffic is routed directly from the airport network interface device 110 along a path 118 to the server 108. The firewall system 114 can also be a part of the airport network interface device 110, as can be obtained conventionally in conjunction with, for example, DSL modems, cable modems, ISDN modems/routers, etc.

For airport equipment which may be sited at locations too distant from the airport server 108 such that hard wire communication is impractical, a wireless communication technology may be implemented. For example, a piece of airfield lighting equipment 101 located at a remote airport location can be configured to accommodate a wireless



transmitting device (not shown) which utilizes an antenna 103 for wirelessly uploading data to the airport server 108, and downloading information from the server, where desired. In this embodiment, radio frequency communication may be utilized.

5 A control center 120 disposed on the GCN 112 provides centralized control and monitor functions for the remote airport 100, and a plurality (2,...,N) of remote airports 122. The control center 120 comprises a central data server 124 which stores all control and monitor data from the remote airports 100 and 122. The data server 124 interfaces to the GCN 112 via a network interface device 125, which network interface device 125 has capabilities similar to that disclosed in reference to network interface device 110 of the  
10 remote airport 100. The central data server 124 also connects to a server control block 126 which provides the control center user interface for the disclosed airport system, including database access of the central data server 124, application and data control for the remote server 108 of the airport 100 through the GCN 112 (and other alternative communication methods disclosed hereinbelow), and remote servers (not shown) of the  
15 remote airports 122.

Communication with the remote airports 100 and 122 is accomplished utilizing a number of methods. As indicated hereinabove, the control center 120 communicates with the remote airports 100 and 122 via the packet-switched GCN 112, or in instances where the GCN 112 may be inoperative, through a circuit-switched Public Switched Telephone  
20 Network (PSTN) 128. A modem 130 provides the interface for communicating over the PSTN 128, and using a switching device 132, alternatively facilitates communication over a wireless path 133, e.g., a cell phone, should the PSTN 128 become inaccessible.

The remote airport 100 has a compatible modem 134 and switching device 136 for utilizing either the PSTN 128 or the wireless path 133, if the GCN 112 becomes  
25 inaccessible. These various methods of maintaining communication with the airports 100 and 122 offer a variety of ways in which to maintain communication between the control central 120 in order to provide control parameters to airport server 108 and data parameters to the subscriber and maintenance contractor under many communication failure conditions. It can be appreciated that communication with the local maintenance  
30 contractor may also be accomplished directly from the airport server system 108 through the PSTN 128, or the GCN 112, or wireless path 133, in contrast to the notification coming indirectly from the remote airport through the control center 120. In this scenario, the fault notifications are stored in the remote server 108 and eventually

transmitted to the data server 124 of the control center 120 for archiving and processing, and provided to the subscriber in accordance with the subscribed level of service.

Other nodes can access the remote airport 100 in accordance with various functions. For example, a sales/marketing node 138 has one or more computers 140  
5 operatively connected to the GCN 112 through a sales network interface 142. The control center 120 hosts a website which is accessible by any node on the GCN 112. However, access to contents of the website is restricted to authorized users by use of a unique password or access code issued to each user. The sales/marketing node 138 is provided access to the website to facilitate illustration of the novel system to potential customers.  
10 Note that there may also be a plurality of such sales/marketing nodes 138 disposed on the GCN 112 which are provided access to the airfield lighting systems of the one or more remote airports (100 and 122).

A contractor node 144 for maintenance personnel who contract to provide support to the remote airport 120 may also be disposed on the GCN 112 to access the website  
15 provided by the control center 120. The contractor node 144 comprises a computer 146 (or other conventional network user interface device) which can access data associated with the remote airport airfield system to determine the status of the airfield lighting system, a contractor network interface device 148 for interfacing to the GCN 112 to facilitate accessing the website provided by the control center 120, and optionally a  
20 modem 150 can be provided as a backup means to the GCN 112 communication path for accessing the airport 100 via the PSTN 128. It can be appreciated that the contractor node 144 may also comprise a wireless solution 152 (e.g., cellular telephone) to facilitate wireless communication directly with the airport system 108 via the wireless path 133 if communication to the website is inaccessible via the GCN 112. However, the primary  
25 communication path is via the GCN 112 to the central control center 120.

A customer node 154 also disposed on the GCN 112 is provided access to the data via the website hosted by the control center 120. The customer node 154 utilizes a customer computer 156 (or other network user interface device) which communicates to the control center website through a conventional customer network interface device 156  
30 across the GCN 112.

The central control center 120 also includes a network access security system to preclude unauthorized access thereto from the various communication paths which provide access thereto. For example, a firewall system is implemented where access via

the GCN 112 is provided. Where dial-up access is provided, various security measures can be utilized, e.g., automatic call-back, user ID/password, etc. Where packet-switched networks are provided (e.g., intranets and extranets), access can be restricted to the unique network interface card ID of the authorized user.

5 Referring now to FIG. 2, there is illustrated a flow chart from the perspective of a customer/client when accessing the disclosed system. When the client subscribes to the disclosed airport system, they are issued at the time of subscription (or prompted to generate at a later time when first accessing the website) an authorization code for future use in logging in to the website in order to access the airport data points. Flow begins at a  
10 function block 200 where the client logs in to, e.g., a mail server (either local or remote mail server) which provides e-mail access to any node on the GCN 112. Flow is then to a decision block 202 to determine if any faults detected at the remote airport have caused e-mail messages to be generated. (Note that notification is not restricted to e-mail messaging, but can be by any number of communication mechanisms, as indicated  
15 hereinbelow.) These e-mail messages can be transmitted to both the client and the maintenance support personnel in order to keep the client informed of any faults detected by the remote airport system. The message, in whatever format, can also be generated for delivery at a time when transmission costs are more favorable. For example, where telephone switched-circuit technology is used, there exist times when the cost of making  
20 such a transmission are less. Of course, the decision to delay such a notification is based upon several factors, for example, the type of failure, such that a nominal failure of a single light may result in the notification being delayed, while a total failure of the all systems causes immediate notification to occur. If an alert was transmitted to the client e-mail address, flow is out the "Y" path to a function block 204 to take action based upon  
25 the alert. The action could include automatically connecting the client node to the website provided by the control center 120 such the client can quickly log in and view the alert and its associated fault, as indicated by the output of function block 204 flowing to a function block 206. If no e-mail message was received, flow is out the "N" path to a function block 206 where the client accesses the website web page. Flow is then to a  
30 function block 208 where the client must enter authorization information in order to gain access to further data related to the remote airport 100. The client can then view the airport data in accordance with the level of service subscribed during the subscription period, as indicated in a function block 210. Note that the disclosed system need not have

a level-of-service program such that the client is provided with total access to all information related to the remote airport 100. Flow is to a function block 212 where the client then logs out of the website, and the process reaches a Stop point.

Referring now to FIG. 3, there is illustrated a flow chart from the perspective of maintenance support personnel when accessing the disclosed system. Flow begins at a decision block 300 where the alert notification monitor system at the maintenance support node 144 continually operates to check for a received alert. The alert notification system includes e-mail, facsimile, a pager, notification via a cellular telephone, etc. If an alert has not been detected, flow is out the "N" path and loops back to the input to continue monitoring for a received alert. If an alert has been received, flow is out the "Y" path to another decision block 302 to determine if the GCN 112 is accessible such that the maintenance personnel can access the remote airport 100 via the website provided by the control center 120 in order to obtain further information of the fault condition. It can be appreciated that this accessing step need not be performed prior to the maintenance personnel being dispatched to the remote airport 100 to correct the fault. However, this feature allows the maintenance staff to better prepare for correcting the fault condition, if it is of a kind which requires expensive replacement parts which may not be stored at the remote airport, or perhaps requires special test equipment in order to troubleshoot and resolve such a fault condition. If the GCN 112 is not accessible, flow is out the "N" path to a function block 304 where the support personnel at the contractor node 144 can use an alternative communication system to obtain more detailed information related to the type of fault condition. For example, a circuit-switched direct-dial connection may be implemented such that the contractor node 144 can communicate directly with the control center data server 124 through the contractor modem 150 via the PSTN 128. If a cell phone is used to contact the control center 120, communication can be through the wireless path 133 using air protocols (WAP - Wireless Application Protocol, and Wireless Java) to the control center modem 130. For example, where the cell phone has a display capability, the contractor can access the control center website using the cell phone such that web clipping can provide a reduced HTML (or other web page development language) visual or text presentation to the contractor regarding the particular fault condition, as indicated in a function block 314. Alternatively, support personnel at the contractor node 144 can communicate directly with remote airport server 108 via the wireless path 133 established between the contractor node antenna 152 and

the remote airport antenna 135. These and other wireless Internet technologies accommodate the wireless transmission of Internet information according to handset geolocation information. (Note that alternative wireless mobile technologies include fixed wireless, broadband wireless (e.g., LMDS - Local Multipoint Distribution System, and MMDS - Multipoint Multichannel Distribution System) and satellite.) Other methods of communication connectivity can be implemented, for example, an intranet or extranet implementation.

Flow continues to a function block 316 where the maintenance personnel are dispatched to the remote airport 100 to correct the fault condition and clear the alert signal. Flow continues to a function block 318 where the support personnel then log the fault information and the repairs performed by entering this information into the airport server 108. The airport server 108 will then upload this information during the next programmed upload cycle. Notably, this repair information may also be entered directly to the control center server 124 via the control center website, where the repair technician logs in to the control center website using any available node in communication therewith, and enters the repair information into a predetermined repair form for archiving. What is important is that this repair information is ultimately archived in the control center server 124 for historical trending related to airfield parts and equipment which have failed. Note that the database of repair information can also be used for inventory control purposes, as discussed in greater detail with respect to FIG. 9. In accordance with the level of service provided to a subscribing customer, this trending information may also be made available to the customer who logs in via the control center website.

Referring again to decision block 302, if the GCN 112 is accessible, flow is out the "Y" path to a function block 306 where the repair technician logs in to the local system at the contractor node 144. Flow continues to a function block 308 where the technician accesses the control center website in order to obtain further information about the fault condition. The technician is then prompted for the authorization information, as indicated in a function block 310, in order to gain access to data related to the fault at the remote airport 100. The technician is then provided the fault information in accordance with the subscribed level of service, as indicated in a function block 312. In an alternative implementation, the e-mail message provides a hyperlink directly to the control center website, or in lieu thereof, provides a detailed description of the fault

condition such that the technician is not further required to log in to the control center website to obtain more detailed fault information. In such an implementation, the e-mail message can be generated to automatically provide all of the fault information needed to properly address the fault condition. As part of generating the e-mail message, the control center data server 124 is automatically accessed to retrieve fault data sufficient to provide the technician the information necessary in correcting the fault condition. This e-mail function can operate in lieu of, or in conjunction with the notification mechanism discussed hereinabove with respect to function block 314. Flow is then to the function block 316 where the technician reports to the remote airport 100 to make repairs and clear the alert. After making repairs, and in order to track failure history, the technician logs the repair information, as indicated in the function block 318. The maintenance process flow then reaches a Stop block.

Referring now to FIG. 4, there is illustrated a flow chart of the operation of the airport notification system, according to a disclosed embodiment. Flow begins at a decision block 400 where the fault notification system of the control center 120 processes recently-uploaded data from the remote airport server 108. If the data indicates that all parameters are within predefined limits, flow is out the "N" path, and loops back to the input to continue monitoring the data. If the data indicates that one or more monitored parameters are out of limits, the corresponding faults are noted. When a fault is detected, the control center system then accesses a database of the data server 124, which database may be the same database which includes the measured parameters of the remote airport 100, and retrieves maintenance personnel information associated with the particular remote airport 122 reporting the fault, as indicated in a function block 402. Additional airport system information may be retrieved at this time in anticipation that some or all of this information will eventually be forwarded to the repair technician as part of the notification alert, or perhaps in response to a later query by the technician for more detailed fault information. Flow is then to a function block 404 where the alert message is generated and transmitted to the repair technician. As mentioned hereinabove, any number of communication methods can be utilized to signal the repair technician at the contractor node 144, including but not limited to, transmission by e-mail via the GCN 112, a pager, cellular phone, personal data assistant, conventional telephone messaging, voice over IP (VoIP), etc. Flow is to a decision block 406 to determine if the GCN 112 is accessible. If not, flow is out the "N" path to utilize any one or more of the

abovementioned communication methods to alert the technician to the fault condition at the corresponding airport, as indicated in a function block 414. Flow then continues to decision block 416 to determine if the repair technician has corrected the fault condition and cleared the alert. If not, flow is out the “N” path to the input of decision block 416 to  
5 continue monitoring the condition until the alert is cleared. If the repair technician has repaired the fault and cleared the alert, flow is out the “Y” path of decision block 416 to a function block 418 where, after the technician has logged all information related to the fault and correction thereof, the control center 120 uploads data from the remote airport server 108 at a predetermined time. This data is then accessible to any authorized user  
10 via the control center website. Flow then loops back to the input of decision block 400 to continue monitoring all remote airport servers 108 (and servers of the corresponding plurality of airports 122) for transmitted fault information.

Referring again to decision block 406, if the GCN 112 is accessible, flow is out the “Y” path to a function block 408 where a message is generated and transmitted (e.g.,  
15 an e-mail message) to the repair technician at the contractor node 144. Note that alert notification by e-mail messaging may provide a sufficient response time for many fault conditions. However, in those instances where more catastrophic failures occur, for example, all airfield lights fail, the fault condition may need to be tagged in accordance with a priority hierarchy. Such a catastrophic failure will then be tagged a high priority  
20 failure, in which case e-mail messaging could be utilized in conjunction with one or more other alert notification methods disclosed hereinabove, or a more immediate notification method, such as paging the repair technician, could be used in lieu thereof. Therefore, if the fault condition is considered a higher priority fault condition, flow is out the “Y” path of decision block 410 to function block 414 to use an alternate communication method in  
25 order to facilitate faster response by the repair technician. Flow from this point follows the discussion detailed hereinabove. If the fault condition is deemed to not be of a high priority, flow is out the “N” path of decision block 410 to a decision block 412 to determine if a confirmation has been received. This can be an optional step to ensure that the repair technician has acknowledged receipt of the alert e-mail message. If not, flow is  
30 out the “N” path to function block 414 to use an alternative communication method of notifying the repair technician, and flow therefrom follows the discussion detailed hereinabove. If an e-mail confirmation was received, indicating that the repair technician acknowledged receipt of the e-mail alert, flow is out the “Y” path of decision block 412

to decision block 416 to determine if the repair technician has cleared the fault condition (i.e., reset the alert flag by repairing the fault condition). Discussion of subsequent branch conditions and steps follows that which was disclosed hereinabove with respect to decision block 416.

5 Referring now to FIG. 5, there is illustrated a flow chart of the operation of the remote airport monitor and control system. Flow begins at a decision block 500 to determine if a fault condition at the remote airport has occurred, and been detected. If so, flow is out the "Y" path to a function block 502 to generate an alert message in accordance with programmed notification parameters, which includes extracting data  
10 from the airport database server 108 in order to identify and notify the corresponding repair technician of the particular fault condition. Note that there can be more than one contractor supporting the various aspects of the remote airport airfield system. For example, there can be a mechanical contractor notified to correct mechanical failures, an electrical contractor which is notified to correct power failures, electronics contractors to notified to correct computer and control system failures, HVAC contractors to correct heating and cooling failures which may be associated with sustaining larger remote airport systems, etc. If no fault is detected, flow is out the "N" path of decision block 500 to a function block 504 to periodically monitor selected data points of the airport airfield system. The rate at which the data points are acquired is performed in accordance with  
15 predetermined programmed criteria. Once the data is acquired from the various measurement points, the data is stored on the airport server 108, as indicated in a function block 506. Flow is then to a decision block 508 to determined if it is time to establish communication with the control center 120 in order to upload the latest airport airfield data to the control center server 124. If not, flow is out the "N" path, and loops back to the input of decision block 500 to continue monitoring for a fault condition. Note that the fault condition may be determined in accordance with the latest set of data acquired by the airport server 108 from the data points, or the fault condition may be directly transmitted to the airport server 108 from the faulty device when the fault occurs, bypassing the periodic data acquisition step routinely executed by the server 108. Such  
20 an immediate notification system could use discrete devices distributed proximate to the data points to be measured such that a processor associated therewith continuously monitors the data wherein an alert can be transmitted as soon as any measured data point falls outside predetermined limits.



Note that it can be appreciated in cases where the data point is remotely located from the airport server 108, a standalone smart device can be utilized having a processor which is programmed to monitor the data points, and to communicate data and alerts to the airport server 108 according to prescribed time intervals, or on a realtime basis.

5 Referring again to decision block 508, if it is time to upload data from the airport server 108 to the control center server 124, flow is out the “Y” path to a function block 510 to establish a communication connection to the control center 120. As mentioned hereinabove, the connection can be by any number of methods, however, in this embodiment, communication is via the GCN 112. Flow is then to a decision block 512 to  
10 determine if the GCN 112 is accessible. If not, flow is out the “N” path to a function block 514 to utilize an alternative communication system as disclosed hereinabove, or in accordance with many conventional communication architectures. Flow is from function block 514 to the input of a function block 516 to upload the data to the control center server 124 by the established communication method. If the GCN 112 is accessible, flow  
15 is out the “Y” path of decision block 512 to the function block 516 to upload the data across the GCN 112 to the control center server 124.

It can be appreciated that the disclosed system also provides the capability of downloading updated programming to the remote airport server 108. For example, if an improved control and data acquisition program update had become available, the update  
20 could be downloaded from the control center server 124 to the remote airport server 108 at the time of uploading the data from the airport server 108. Alternatively, the updated program could be downloaded at times when airport traffic is determined to be the least likely to occur such that any possible programming problems would not interfere with operation of the remote airport system. Continuing with the flow chart, flow is then to a  
25 decision block 518 to determine if updated programming is available for download. If not, flow is out the “N” path, and loops back to the input of decision block 500 to continue monitoring of fault conditions. If updated programming is available for download, flow is out the “Y” path of decision block 518 to a function block 520 to commence the program transfer. Flow is to a function block 522 to then restart the  
30 program code, where necessary, and where airport airfield operation is least likely to be interrupted should a program problem occur. Flow then loops back from function block 522 to the input of decision block 500 to continue monitoring for fault conditions.

Referring now to FIG. 6, there is illustrated a flow chart of control center system

operation from the perspective of the control center when a user accesses the disclosed system. Flow begins at a function block 600 where a user establishes communication across the GCN 112 to the control center website. Note the user can be a user from the customer node 154, the maintenance contractor node 144, the sales/marketing node 138, a user from the remote airport 100, etc. Connectivity can be established from virtually any user disposed on the GCN 112 who has a network user interface device which executes a communication application (e.g., a browser) compatible for interfacing to the control center website. It is also conceivable that the data stored on the control center data server 124 is accessible using a file transfer protocol which retrieves information in a non-HTML (or browser) format. The user is then prompted for authorization information, as indicated in a function block 602. Flow is to a decision block 604 to determine if the entered authorization information is valid. If not, flow is out the "N" path to a function block 606 to notify the user that an error has occurred, and to, for example, re-enter the authorization information. Flow then loops back to the input of decision block 604 to check the entered authorization again. If multiple entry failures have occurred, the user can be locked out from further access and instructed to contact the system provider.

If the entered authorization information is valid, flow is out the "Y" path of decision block 604 to a function block 608 to perform a database query in accordance with the valid authorization information. The query establishes the association with the data which is to be presented to the authorized user, and where levels of service are provided, presents only that information to which the user is subscribed. For example, if the authorization information indicated a user at the sales node 138, the data presented to prospective customers could be that associated with a demonstration application operating on the accessed control center server 124. Alternatively, or in conjunction therewith, the sales staff can be provided access to actual data from the remote airport 100. In any case, the level of access provided to the extensive features of the disclosed airport system is provided in accordance with the authorization (or login) information. Flow then reaches a Stop block.

Referring now to FIG. 7, there is illustrated a user interface of an authorization web page to the control center website. The user interface is via a conventional network communication program (e.g., a web browser). The authorization web page 700 contains standard features for providing authorized access to further information. For example, the web page contains a site path information field 702 which indicates the current

Uniform Resource Locator network address of the web page 700. A menu field 704 provides various application functions which can be used by the user. A navigation bar 706 allows the user to move both forward and back through web pages which have already been downloaded from the control center data server 124 to the user computer (e.g., computer 140, 156, etc.). The web page 700 also includes an address field 708 which allows the user to enter a network address of a node on the GCN 112 to which the user may want to connect. An active link field 710 presents the network address of one or more active links embedded into the web page.

A main body area 712 of the web page 700 comprises text 714 which may, for example, provide a greeting to the user, and instruct the user to perform certain steps in order to obtain further information. In this scenario, the text 714 instruct the user to enter an authorization code in a code field 716 before further access is provided. As indicated hereinabove, the authorization code is provided to the user (e.g., the customer, contractor, sales person, etc.) when an account is opened for the customer. The authorization code is unique to each entity, but may provide access to the same information stored in a server database (e.g., the database of the control center data server 124). The authorization code may be a single alphanumeric character string, or could be a combination of a user ID and password, or any other type of conventional access authorization methods provided by network web sites.

The authorization web page 700 may also include an ad space 718 which provides fixed or rotating advertisements to the user. The ads 718 comprise information which informs the user of new updates to system, or other informational functions such as products associated with the system provider, etc. It can be appreciated that where cookies are allowed on the user computer system, whether it be the customer, contractor, sales personal, etc., the ads 718 can be customized to provide information of interest to the particular user. For example, if the user is a customer at the customer node 154 connected from California, and the remote airport is located in Minnesota, the ads 718 presented could be triggered to such geographic information to provide weather reports based upon seasonal changes, which are not a concern in California, but which may significantly impact operation of the airport airfield system in Minnesota. Similarly, where the user is a maintenance contractor, the ads 718 could be trigger in response to the contractor cookie information to present recent updates in system hardware or software which are of interest only to the contractor, or advertise recent developments in

troubleshooting hardware, or airfield lighting improvements which could be purchased by the system provider.

Note that this customized advertising can also be triggered based upon the unique user authorization code, such that the information is provided on a subsequent web page, and in greater detail according to specific user interests and the remote airport(s) being monitored. The extent of the messaging via the advertisement area 718 can accommodate a wide variety of information including paid advertising for related products.

Referring now to FIG. 8, there is illustrated a follow-up data web page 800 to the authorization web page 700 showing various data parameters which can be accessed by a user. The primary difference between the information of this web page and the previous authorization web page 700 is contained within the body area 712. After the user authorization code has been validated, the data web page 800 is presented to the user with various data parameter information about the status of the remote airport airfield system selected. If the remote airport airfield system had ten CCR front-end systems for monitor and control of airfield lighting, data regarding each CCR could be listed on the data web page 800 along with an associated status field. For example, a first CCR 802 is listed, and has associated therewith a data field 804 in which a corresponding data parameter can be placed in a numerical format to indicate the state of that light system. Alternatively, the data can be automatically interpreted by software such that a general status text (e.g., “ok” or “failed”) is provided, when the particular CCR 106 is operating properly. Other data can also be provided, for example, measured parameters related to dielectric integrity 806 of the series system are retrieved from the control center data server 124 and inserted into a corresponding dielectric field 808 for presentation to the user. Additionally, an information area 810 can be provided for presenting detailed information to the user. Since the user has already passed the authorization stage, information provided in the information area 810 can be sufficiently detailed, e.g., to inform the user regarding account information, hardware/software historical data, etc. It can be appreciated that the information provided herein is solely at the discretion of the system provided and the user.

In an alternative embodiment, the type of information provided can be based upon the authorized user. For example, if the user is a sales person, the level of detail provided in the data fields 804 may be in a go/no-go format, e.g., “ok” or “failed, whereas if the user was a repair technician, the data would be actual numerical values which are more

useful in determining the true state of the remote airport system. It can be appreciated that numerous options can be provided to the specific users of the web portal based upon a number of factors, and the availability of the options can be based upon a subscribed level of service, or each user can have full access, etc.

5           Where the customer has several remote airports 122 under monitor and control utilizing the disclosed system, the web page 800 can include data for both airports on the same web page 800 if sufficient web page real estate exists, or an active link 812 can be provided, which when selected by the user, presents another web page (not shown) of data and information associated with that remote airport 122.

10           Referring now to FIG. 9, there is illustrated a database structure 900 of account information and data parameters which may be archived, in accordance with a disclosed embodiment. As indicated hereinabove, numerous pieces of information may be stored in association with a user in the database of the control center data server 124 for later retrieval and presentation. For example, in this particular database example, an  
15           authorization code field 902 provides a primary association with the remote airport 100 by linking the authorization code with data of the particular remote airport 100. When the user enters an authorization code, a variety of associated information is made available for presentation to the user. This associated information is also accessed when a fault condition is detected, such that when an airport code 903 is known, the  
20           corresponding contact information for the repair technician (and/or other designated persons) can be retrieved for establishing communication thereto. As illustrated, the contact information comprises an e-mail field 904, a pager field 906, and telephone number field 908. Other contact information can also be provided, as mentioned hereinabove, for example, a facsimile number, a cellular telephone number, a network  
25           address to a PDA device, etc.

          The database 900 also includes a service level field 910 which defines the level of subscribed service, where such an option is provided. For example, a first customer 912 (Cust1) may have subscribed to a level of service (e.g., level 1) which includes presenting status data parameters 911 of a general nature (e.g., "ok") with respect to a corresponding  
30           remote airport airfield system, and does not present, for example, trending information which is provided at a different level (albeit more costly) of service (e.g., level 4), specific parameter values, etc. Many different options for data manipulation can be provided limited only by the robustness of the underlying applications which process the

data and support the control center web site. It can be appreciated that the information presented to the a repair technician (Repair1) associated with a repair field 914 can be more specific to facilitate problem resolution. Note that a single customer (Cust1) may have the same authorization code for accessing multiple remote airports (e.g., aaaa and  
5 xxxx) for which service is subscribed.

The database associated with the data server 124 can also store maintenance and parts information such that as the maintenance technician orders and uses parts or components from inventory, the part can be tracked as to the location at which it is used. The maintenance database can also operable to track the inventory to automatically  
10 trigger replenishment by notifying an individual to order sufficient parts to bring inventory of those parts or components back to a minimum level. The data server is also operable to automatically notify, for example, a central inventory warehouse to ship a replacement part when the cause of a fault is detected by the disclosed system. The data server 124 can also cross-check the availability of the failed component against an  
15 inventory database of parts or components stored locally to the airport to first determine if the part can be obtained from a local inventory or needs to be ordered-in from a remote location.

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein  
20 without departing from the spirit and scope of the invention as defined by the appended claims.